



## AVM System 240 Micro Topping 240 For Concrete Floors

Components			
	System Materials		
	Aggregate 240 50 lb. bag (Dry Mix)	Primer 100 5 gal. bucket	Top Coat Sealer 5 gal. bucket
Coverage/item	80 sq. ft. @ 1/16"	1,000-1,500 sq. ft.	200 sq. ft. per gallon
AVM Part No.	240-W or 240-G	Prim100-5	Top Coat Sealer
Approx. Weight	50 lbs.	46 lbs.	47 lbs.
Coverage Chart/Estimating Tool (Qty. Required)			
100 sq. ft.	2	1	1x(2G)
200 sq. ft.	3	1	1x(2G)
500 sq. ft.	7	1	1
750 sq. ft.	10	1	1
1,000 sq. ft.	13	1	1
1,500 sq. ft.	19	2	2
2,000 sq. ft.	25	2	2
3,000 sq. ft.	38	3	3
4,000 sq. ft.	50	3	4
5,000 sq. ft.	63	4	5
10,000 sq. ft.	125	8	10

### Notes

- Quantities are approximate. Coverages may vary based on field, weather and other conditions.
- (2G) means a 2 gallon bucket.
- 3x(2G) means three, 2 gallon buckets are needed, or a total of 6 gallons.
- When a part number ends with a -5, it means the product comes in a 5 gallon bucket.
- When a part number ends with a -2, it means the product comes in a 2 gallon bucket
- 240-W means white cement in the bag and 240-G means grey cement in the bag.

### Other Components

- AVM Acripatch 5020

### Recommended Tools

- Brush 4"
- Paint Roller (9" Frame) with 1" nap roller cover
- Taping Knife 8" (Scraper)
- Cutting Knife
- Trowel
- Mechanical Blower or Broom
- Drill and Mixing Paddle

### Optional Tools

- Hopper-Gun (for spraying texture)
- Small Compressor
- Caulking Gun

