



AVM System 750 AVM Yellow

Anti-Fracture Membrane for Under-Tile Waterproofing

Components

	Materials for the Waterproofing Membrane					Materials for Optional Protective Coating		
	AVM Yellow 1 gal. bucket	AVM Yellow 5 gal. bucket	Mat 800 6"x300 ft.	Mat 800 40"x81 ft.	Mat 800 40"x324 ft.	AVM Aggregate 200 50 lb. bag	Additive 7700 2 gal. bucket	Additive 7700 5 gal. bucket
Coverage/item	40 sq. ft.	190 sq. ft.	300 linear ft.	250 sq. ft.	1080 sq. ft.	80 sq. ft. @ 1/16"	Use 1.0-1.25 gal./ bag	Use 1.0-1.25 gal./ bag
AVM Part No.	75010	75050	Mat800-06/100	Mat-Kit 250	Mat800-40/324	200-G	ADD7700-2	ADD7700-5
Approx. Weight	10 lbs.	48 lbs.	3.2 lbs.	10 lbs.	22.6 lbs.	50 lbs.	18 lbs.	46 lbs.

Coverage Chart/Estimating Tool (Qty. Required)

40 sq. ft.	1			1 (See Note 2)		1	1	
120 sq. ft.	3			1 (See Note 2)		2	1	
250 sq. ft.	2	1		1 (See Note 2)		3	2	
500 sq. ft.		3		2 (See Note 2)		6	1	1
750 sq. ft.		4		3 (See Note 2)		10		2
1,000 sq. ft.		5	1 (See Note 2)		1 (See Note 2)	13		3
1,500 sq. ft.		8		2 (See Note 2)	1 (See Note 2)	19		5
2,000 sq. ft.		10	1 (See Note 2)		2 (See Note 2)	25		6
3,000 sq. ft.		16	2 (See Note 2)		3 (See Note 2)	38		8
4,000 sq. ft.		22	2 (See Note 2)		4 (See Note 2)	50		12
5,000 sq. ft.		27	3 (See Note 2)		5 (See Note 2)	64		16
10,000 sq. ft.		54	5 (See Note 2)		10 (See Note 2)	128		32

Notes

- Quantities are approximate. Coverages may vary based on field, weather and other conditions.
- Refer to AVM's details, specifications and installation instructions for information about when to use reinforcement mats.

Other Components

- Caulking. Construction grade caulking such as "Sika Flex 1A" or Equal.
- AVM Primer 500
- AVM Crete 6700 (Protective Coating)
 - Additive 7700
 - Aggregate 200-G, 50 lb. bag

Recommended Tools

- Brush 4"
- Paint Roller (9" Frame) with 1" nap roller cover
- Taping Knife 8" (Scraper)
- Cutting Knife
- Trowel
- Mechanical Blower or Broom
- Drill and Mixing Paddle

Optional Tools

- Caulking Gun
- Sprayer

