


IAPMO RESEARCH AND TESTING, INC.

5001 East Philadelphia Street, Ontario, California 91761-2816 • (909) 472-4100 Fax (909) 472-4244 • www.iapmo.org



CERTIFICATE OF LISTING

IAPMO Research and Testing, Inc. is a product certification body which tests and inspects samples taken from the supplier's stock or from the market or a combination of both to verify compliance to the requirements of applicable codes and standards. This activity is coupled with periodic surveillance of the supplier's factory and warehouses as well as the assessment of the supplier's Quality Assurance System. This listing is subject to the conditions set forth in the characteristics below and is not to be construed as any recommendation, assurance or guarantee by IAPMO Research and Testing, Inc. of the product acceptance by Authorities Having Jurisdiction.

Effective Date: August 2010

Void After: August 2011

Product: Shower Pan Liner

File No. 5003

Issued To: AVM Industries Inc.
8245 Remmet Avenue
Canoga Park, CA 91304

IDENTIFICATION: Manufacturer's name or trademark, and the cUPC® certification mark.

CHARACTERISTICS: Load bearing, bonded, waterproof membranes for thin-set ceramic tile and dimension stone installation. To be installed in accordance with the manufacturers instruction and the latest Uniform Plumbing Code and jurisdictional requirements in Canada.

NOTE: These models are listed for Canadian requirements to the same ANSI A118.10-99 standard.

Products comply with the applicable sections of the latest edition of the Uniform Plumbing Code® and the International Plumbing Code®. Models listed to the National Plumbing Code of Canada and Relevant Canadian Standard(s) shall bear the cUPC mark of conformity. Manufactured in compliance with ANSI A118.10-2008.

Products listed on this certificate have been tested by an IAPMO R&T recognized laboratory. This recognition has been granted based upon the laboratory's compliance to the applicable requirements of ISO/IEC



Chairman, Product Certification Committee


CEO, The IAPMO Group

For the most accurate and updated information please visit <http://pid.iapmo.org/5003>

This listing is for the period indicated herein and is void after the date shown above. Any change in material, manufacturing process, marking or design without having first obtained the approval of the Product Certification Committee, or any evidence of non-compliance with applicable codes and standards or of inferior workmanship, may be deemed sufficient cause for revocation of this listing. Reproduction of or reference to this form for advertising purposes may be made only by specific written permission of IAPMO Research and Testing, Inc. Any alteration of this certificate could be grounds for revocation of the listing.






IAPMO RESEARCH AND TESTING, INC.
CERTIFICATE OF LISTING

Page 2

Void After: August 2011

Product: Shower Pan Liner
Issued To: AVM Industries Inc.
17025.

File No. 5003



IAPMO RESEARCH AND TESTING, INC. CERTIFICATE OF LISTING

Page 3

Void After: August 2011

Product: Shower Pan Liner
Issued To: Avm Industries Inc.
MODELS:
AVM System 750

File No. 5003



Report Number: 0131
Issued: 09/2009
Expires: 09/2011

DIVISION: 07-THERMAL AND MOISTURE PROTECTION

Section: 07 10 00-Dampproofing and Waterproofing

Section: 07 14 00-FLUID APPLIED WATERPROOFING

DIVISION: 09-FINISHES

Section: 09 30 00-Tiling

Section: 09 31 00-Thin-Set Tiling

Section: 09 34 00-Waterproofing-Membrane Tiling

REPORT HOLDER:

AVM INDUSTRIES, INC.
8245 REMMET AVENUE
CANOGA PARK, CALIFORNIA 91304-4133
(818) 888-0050

www.avmindustries.com
amir@avmindustries.com

EVALUATION SUBJECT:

AVM SYSTEM 750 WATERPROOF MEMBRANE

1.0 EVALUATION SCOPE

1.1 Compliance with the following codes:

- 2006 *International Building Code*® (IBC)
- 2009 *International Plumbing Code*® (IPC)
- 2009 *Uniform Plumbing Code*® (UPC)
- 1997 *Uniform Building Code*™ (UBC)

1.2 Evaluated in accordance with:

- ANSI A118.10-2008

Properties evaluated:

Water resistance

2.0 USES

The AVM System 750 is used on concrete or plywood floors as a barrier to liquid water migration in bonded thin-set installations of ceramic tiles and dimension stone under the IBC and IRC. The membrane is also used as a shower sub-panlining material in accordance with the IPC and the UPC.

3.0 DESCRIPTION

3.1 General:

The AVM System 750 is a liquid-applied waterproofing membrane that cures to a monolithic, elastomeric membrane.

3.2 Materials:

3.2.1 AVM Paste 750: AVM Paste 750 (liquid) is a ready-to-use, water-based paste, packaged in 5-gallon (18.9 L) pails. Shelf life is one year from the date of manufacture when stored unopened at temperatures between 50°F and 90°F (10°C and 32°C). The liquid material must not be allowed to freeze.

3.2.2 Optional - AVM Mat 800 Fabric Reinforcement: AVM Mat 800 reinforcing fabric is a 3.0-ounce-per-square-yard (101.7 g/m²) fabric for use as a reinforcement in the AVM System 750 membrane when needed. The fabric is provided in 40-inch-wide-by 324-inch-long (1016 mm by 98 755 mm), 1080-square-foot (99.3 m²) rolls. Refer to manufacturer's instructions on where and when to use reinforcing fabric.

3.2.3 AVM Mat 800 Reinforcing Tape: AVM Mat 800 reinforcing tape is a 3.0-ounce-per-square-yard (101.7 g/m²) fabric for use in preparing joints, cracks and corners in the substrate before application of the AVM System 750 membrane. The tape is provided in 6-inch-wide-by-300-foot-

long (152 mm by 91.4 m) rolls.

3.2.4 AVM Crete 6700: AVM Crete 6700 is a field-mixed cementitious product composed of AVM Aggregate 200 mixed with the AVM Additive 7700.

3.2.5 AVM Additive 7700: AVM Additive 7700 (liquid) is a ready-to use, water-based acrylic latex packaged in 5-gallon (18.9 L) pails. Shelf life for the AVM Additive 7700 is one year from the date of manufacture when stored unopened at temperatures between 50°F and 90°F (10°C and 32°C). The liquid material must not be allowed to freeze.

3.2.6 AVM Aggregate 200: AVM Aggregate 200 is a proprietary mix of cement and sand aggregates, packaged in 50-pound (22.7 kg) bags.

3.2.7 AVM Primer 500: AVM Primer 500 (Liquid) is a ready-to use, water-based primer packaged in 5-gallon (18.9 L) pails. Shelf life for the AVM Primer

500 is one year from the date of manufacture when stored unopened at temperatures between 50°F and 90°F (10°C and 32°C). The liquid material must not be allowed to freeze.

4.0 INSTALLATION

4.1 General:

Installation of the AVM System 750 membrane must comply with this report and the manufacturer's published installation instructions. The manufacturer's installation instructions must be available at the jobsite at all times during installation.

4.2 Surface Preparation:

Substrates must be clean and free of all oils, greases and other contaminants. Dry and dusty surfaces must be dampened and swept off. All cracks, joints and corners are treated by covering them with the AVM Mat 800 reinforcing tape embedded into AVM Paste 750. A second layer

of AVM 750 reinforcing tape is applied to critical areas subjected to stress or movement. All existing surfaces must be flat or leveled with a minimum slope of one-fourth unit vertical in 12 units horizontal (2 percent slope), and all defects repaired. Newly prepared concrete must be cured 28 days prior to application of the AVM System 750, and the surface must be troweled smooth then textured to a fine broom finish.

4.3 Application over Concrete Substrate:

After preparation of the concrete substrate, AVM Primer 500 is applied to the concrete surfaces using a brush or roller. After the primer has cured, (dry to the touch) AVM Paste 750 is applied to the concrete in three coats with a brush or roller. The first coat is applied at a coverage rate of 1 gallon per 100 square feet (0.41 L/m²).

After the first coat has cured (The first coat needs to be dry a minimum of two hours and until it's dry to the touch and had changed color from light yellow to orange). The second coat is applied at a coverage rate of 1 gallon per 100 square feet (0.41 L/m²).

After the second coat has cured (The second coat needs to be dry a minimum of two hours and until it's dry to the touch and had changed color from light yellow to orange). The third coat is applied at a coverage rate of 1 gallon per 100 square feet (0.41 L/m²).

Membrane dry thickness must be a minimum 40 mils [0.040 inch (~1.00 mm)] If not, continue applying coats as needed until the minimum thickness is achieved.

After the last coat is applied, the membrane must be allowed to dry a minimum of 24–48 hours before performing a water test or prior to the application of ceramic tile, dimension stone or other finished surfaces. (Curing times may vary based on temperature, humidity and other factors)

The AVM Crete 6700 protective coating is optional. The protective Coating, consisting of



Report Number: 0131
Issued: 09/2009
Expires: 09/2011

Aggregate 200, is field-mixed with 1.0 to 1.25 gallons (3.8 to 4.7 L) of AVM Additive 7700, and is applied to the membrane using a trowel. The protective coating must cure a minimum of 24 hours before application of ceramic tile or dimension stone.

The membrane without the protective coating must not be exposed to direct sunlight for more than 30 days. Furthermore, the membrane without the protective coating should have tile, stone, etc installed on it within 30 days from the membrane installation date. The membrane with the protective coating installed over it must be covered with tile, stone etc, within 90 days from the membrane installation date. Ceramic tile must comply with ANSI A137.1.

4.4 Application over Plywood Substrate:

After preparation of the plywood substrates, when the AVM System 750 is applied directly over plywood, the first coat of Paste 750 is applied at a coverage rate of 1 gallon per 100 square feet (0.41 L/m²). While the paste 750 is still wet, AVM Mat 800 reinforcing fabric is embedded into the liquid. The fabric must overlap 2 inches, (51 mm) at seams at edges and ends. Immediately after embedding the fabric and while the Paste 750 is still wet, apply another coat of the AVM Paste 750 over the fabric to sandwich it in at a coverage rate of 1 gallon per 100 square feet (0.41/m²). At this point allow the membrane to cure for 24 hours. Then apply a third coat of the AVM Paste 750 at a coverage rate of 1 gallon per 100 square feet (0.41 L/m²). Allow to cure until dry to the touch and check thickness. Membrane dry thickness must be a minimum 40 mils thick. [0.040 inch (~1.00 mm)] If not, continue applying coats as needed until the minimum thickness is achieved. Once the membrane has reached the needed thickness, it must be allowed to dry a minimum of 12 hours before application of the protective coating. When the AVM System 750 is applied directly to horizontal plywood substrates, AVM Crete 6700 (protective coating) must be applied over the cured membrane to a minimum thickness of 1/16 inch (1.6 mm). The protective coating, consisting of Aggregate 200, is field-mixed with 1.0 to 1.25

gallons (3.8 to 4.7 L) of AVM Additive 7700 and is applied to the cured membrane using a trowel. The protective coating must cure a minimum of 24 hours before application of ceramic tile or dimension stone.

4.5 Method of Repair

The membrane in the area requiring repair must be removed and cleaned, allowing for a minimum 2-inch (51 mm) overlap. The membrane and protective coating (if needed) are applied as described in Sections 4.3 and 4.4.

5.0 CONDITIONS OF USE

The AVM System 750 Waterproof Membrane described in this report complies with, or is a suitable alternative to what is specified in, those codes listed in Section 1.0 of this report, subject to the following conditions:

5.1 The materials are applied in accordance with this report and the manufacturer's published installation instructions. In the event of a conflict between the installation instructions and this report, consult with the manufacturer for the latest updates.

5.2 Application is limited to ceramic tile and dimension stone installation on floors and walls and to use as a shower pan lining.

5.3 Application over expansion joints is outside the scope of this report.

6.0 EVIDENCE SUBMITTED

Data in accordance with ANSI A118.10-2008.

7.0 IDENTIFICATION:

Each container of AVM Paste 750 bears a label with the AVM Industries, Inc., name and address, the product name, the date of manufacture and the IAPMO Evaluation Report number and ES mark of conformity.

EVALUATION REPORT



Report Number: 0131
Issued: 09/2009
Expires: 09/2011

Each container of Additive 7700 bears a label with the AVM Industries, Inc., name and address, the product name, the date of manufacture, IAPMO Evaluation Report number and ES mark of conformity.

Each bag of AVM Aggregate 200 bears a label with the AVM Industries, Inc., name and address, the product name, and a batch number tied to the date of manufacture.

The large rolls (40" wide / 88 C"M wide) of fabric reinforcement are identified with the AVM Industries, Inc., name and the words "AVM MAT 800," or will have their respective manufacturers labels on them. Small rolls (6" wide / 13 C"M wide) rolls will not have any labeling on them.



IAPMO # 0131

A handwritten signature in black ink, appearing to read "Dennis Hill".

Director of Evaluation Services