



AVM Primer 570

Asphaltic / Bituminous Roofing & Waterproofing Primer

Asphaltic Primer Spec

Section 071400 –
Fluid-Applied Waterproofing
Section 071413 – Hot Fluid-Applied
Rubberized Asphalt Waterproofing
Section 075556 – Hot-Applied Rubberized
Asphalt Protected Membrane Roofing

Product Name

AVM Primer 570

By

AVM Industries, Inc.
8245 Remmet Ave, Canoga Park, CA 91304
888.414.1041 818.888.0050
www.avmindustries.com

Product Description

AVM Primer 570 is an asphaltic / Bituminous Roofing & Waterproofing Primer which provides deep penetration and will promote adhesion of AVM's Asphaltic / Bituminous Waterproofing membranes.

VOC 350 G/L

AVM primer 570 Meets VOC requirements established for Bituminous Roof Primer category of Architectural Coatings.

Where to Use

Over new or existing concrete substrates, masonry, existing mortar, exterior grade plywood, metal and gypsum.

Submittals

When applicable, submit this Technical Data Sheet along with the appropriate waterproofing system documentation.

Warranty

AVM standard 1 year warranty applies only if used as part of an AVM system.

Delivery, Storage, and Handling

- Delivery of the AVM Primer 570 materials to the job site must be in their original sealed containers with manufacturer's name and label intact.
- Handle and store containers in accordance with printed instructions.
- Store at temperatures between 40°F and 90°F. Do not store materials in direct sunlight or where they may be damaged by water or rain. Bags must be kept dry!
- Keep all materials out of the reach of children.
- Store in a well-ventilated place. Store locked up.
- If irritation occurs during use, liberally flush affected areas with water. If irritation continues, see a physician immediately.



Project Conditions

- Do not apply materials at temperatures below 40°F, or if precipitation is imminent, or above 100°F if applying in direct sun light.
- Provide adequate ventilation during installation.
- Warn personnel against hazards of materials to skin and eyes.
- Protect adjacent surfaces which could be damaged during the application.
- This system must not be used to cover Expansion Joints.

Surface Preparation

Be sure all substrates are dry, clean and free from oil, grease, rust scale, loose paint, dirt, dust and debris that would interfere with surface contact and act as a bond breaker.

Mixing Instructions

Mix bucket contents well before use.

Application:

Apply using a roller, brush or spray. Follow installation instructions of the waterproofing system being installed.

Coverage may be as high as 300 Sq. Ft. per gallon on smooth surfaces. Rough surfaces or surfaces with higher absorbency may yield lower coverage rates.

Quality Control

- Visually inspect all coated surfaces to ensure a full and proper coating application, especially at corners, drainage scuppers and hard-to-reach areas.
- All unsatisfactory areas shall be re-primed prior to waterproofing system application.
- If over 24 hours, re-prime.

Protection of Installed Work

The completed section shall be protected from all pedestrian traffic for the first 24 hours after application and until the surface is sufficiently cured. (The amount of drying time may vary depending on temperature and humidity conditions) Typically, light foot traffic may resume after 4-6 hours.

Clean Up

Tools may be cleaned with solvent.

Availability and Cost

Contact AVM Industries or your approved applicator for pricing and availability.

Technical Services

Technical services are available by contacting our offices at: **888.414.1041** or **818.888.0050** or visit **www.avmindustries.com**

System Specifications

See next page.

The following coverages are based on controlled tests. Actual coverages may vary.

General Data - AVM Primer 570		
Shelf Life:	One year in original unopened packaging.	Storage: Store dry at 40°F - 90°F.
Dry Time:	Dry to the touch time @ 72°F 45 minutes	Flash Point: >105°F

Packaging	Approx. Shipping Weights	VOC
4.7 gal. pails	40 lbs.	350 Grams/Liter

For a complete list of details in CAD or PDF, please visit our website at www.avmindustries.com.

AVM Industries, Inc.
8245 Remmet Ave, Canoga Park, CA 91304
888.414.1041 818.888.0050

Quality Waterproofing Products



www.avmindustries.com