# Material Safety Data Sheet AVM Aussie Skin 550 Tape

## [1] PRODUCT AND COMPANY IDENTIFICATION

Product Name: Aussie Skin 550 Tape
Company: AVM Industries, Inc.

8245 Remmet Ave, Canoga Park, CA 91304

Tel: (818) 888-0050 www.avmindustries.com

# [2] COMPOSITION / INFORMATION ON INGREDIENTS

	Component %	CAS No
Rubber chips	28 %	68071-29-4
Polybutene	11%	9003-28-5
Wang resin	40%	201058-08-4
Agent	11%	
Others	10%	

## Inhalation

The product is not likely to cause effects on the respiratory system. If the Tape is torch-applied, asphalt fumes can be emitted of the product and cause irritations to the nose, the throat and the respiratory tracts, tiredness, headaches, dizziness, nauseas and insomnia.

#### Ingestion

Exposure is not likely to occur by this route of entry under normal use of the product.

#### **Skin Contact**

The repeated or prolonged contact will not cause irritation. If the tape is torch-applied, asphalt fumes can be emitted. The long-term exposure to the asphalt fumes can cause changes of the pigmentation of the skin which can be worsened by the exposure to the sun.

#### **Eye Contact**

The product is not likely to cause effects to the eyes. If the tape is torch-applied, asphalt fumes can be emitted of the product and cause irritations, redness and conjunctivitis to the eyes. The contact with this product at high temperature can cause thermal burns.

## [3] First-aid Measures

#### Inhalation

Remove to fresh air. Give oxygen / artificial respiration if needed. Consult Doctor.

## Ingestion

Do not induce vomiting.

## **Eye Contact/Skin Contact**

Remove contaminated clothing. Apply proprietary skin cleaner,

# [4] Fire-fighting Measures

#### **Extinguishing Media**

Dry powder, CO2, Earth, Sand, Foam. Do not use Water.

#### **Special Fire Fighting procedures**

Wear self-contained breathing apparatus, Full protective clothing. Spray drums with Water to keep cool.

## **Unusual Fire & Explosion Hazards**

Vapor is heavier than air. Combustion Produces toxic gases

## [5] Accidental Release Measures / Spills and Leaks

## Steps to be taken in case material is released or spilled

Absorb onto inert material, e.g. sand, earth. Put into suitable containers. Prevent from entering water ways

## [6] Handling & Storage

## Precautions for safe handling

Keep in tightly closed containers out of direct sunlight, in a cool dry area and away from all sources of ignition. Store between  $50^{\circ}$ F and  $90^{\circ}$ F

# Other precautions

Store away from oxidizing agents, peroxides, Food stuffs

# [7] Exposure Controls / Personal Protection

## **Respiratory Protection (Type)**

Self-contained breathing apparatus if in enclosed spaces. Otherwise, not normally required.

## [8] Ventilation

#### **Local Exhaust**

Ensure adequate ventilation to comply with OEL.

Protective Gloves Rubber, PVC

**Eye Protection** Safety goggles Long sleeved shirts

## [9] Physical & Chemical Properties

**Appearance:** transparent flashing tape Glue Shape

рΗ N/A **Boiling Point/Boiling range °C** N/A **Specific Gravity** N/A Vapor pressure (MM mercury) N/A **Melting Point / Freezing point** N/A **Water Solubility** Insoluble Viscosity N/A Percentage Volatile by volume % N/A **Evaporation Rate (Butyl Acetate=1)** N/A Flash Point °C / Method used N/A **Lower Explosive limits** NA **Upper Explosive limits** NA

# [10] Stability & Reactivity

Stability Stable under normal conditions

Conditions to avoid High temperatures

Incompatibility/Materials to avoid Oxidizing agents, strong acids, alkalis, Halogens

Hazardous Decomposition Products Combustion produces toxic gases

Hazardous Polymerization Will not occur

## [11] Toxicological Information

No information available on this product

## [12] Ecological Information

No data, This product is not biodegradable. No possible bio-accumulation and unlikely bio-concentration in the food chain.

## [13] Disposal Consideration

This product is not hazardous waste. Consult local, and state for proper disposal methods

## [14] Transport Information

Class This product is not regulated by Department of Transportation

## [15] Regulatory Information (Risk & Safety Phrases)

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic Environment Wear suitable protective clothing, gloves and eye / face protection

## [16] Other information

# **CALIFORNIA PROPOSITION 65:**

THIS MATERIAL MAY CONTAIN SUBSTANCES KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER OR REPRODUCTIVE DEFFECTS.

The contents and format of this MSDS are in accordance with ISO Commission Directive ISO11014-1:1994.

**DISCLAIMER:** The information contained herein is, to the best of our knowledge and belief, accurate and current as of the date of this MSDS. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. All chemicals may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist. Final determination of suitability of the chemical is the sole responsibility of the user. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or any other nature are made hereunder with respect to the information contained herein or the chemical to which the information refers. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations.