Safety Data Sheet

AVM Industries Inc.

Version 1.1 Revision Date 8-5-15

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Paste 750 Product Code: 750 Paste

Trade Name: Paste 750

AVM Industries, Inc.

8245 Remmet Ave, Canoga Park CA 91304-4133

Tel: (818) 888-0050 www.avmindustries.com **Emergency Contact:**

AVM Industries, Inc. Tel: (818) 888-0050

2. HAZARDS IDENTIFICATION

GHS Ratings:

Eye corrosive	2A	Eye irritant: Subcategory 2A, Reversible in 21 days
Carcinogen	1A	Known Human Carcinogen Based on human evidence
Organ toxin single exposure	3	Transient target organ effects- Narcotic effects- Respiratory

tract irritation

1 Significant toxicity in humans- Reliable, good quality human Organ toxin repeated exposure

case studies or epidemiological studies Presumed significant toxicity in humans- Animal studies with significant and/or severe toxic effects relevant to humans at generally low

exposure (guidanc

GHS Hazards

H319	Causes serious eye irritation
H335	May cause respiratory irritation
11050	M

H350 May cause cancer

H372 Causes damage to organs through prolonged or repeated exposure

GHS Precautions

D204

P201	Obtain special instructions before use
P202	Do not handle until all safety precautions have been read and understood

P260 Do not breathe dust, mist or vapours P261 Avoid breathing dust, mist, or vapours

P264 Wash hands, forearms and face thoroughly after handling P270 Do not eat, drink or smoke when using this product P271 Use only outdoors or in a well-ventilated area

P280 Wear protective gloves, protective clothing, eye protection, and face protection

SDS for: 750 Paste Page 1 of 5 P281 Use personal protective equipment as required

P312 Call a POISON CENTER or doctor/physician if you feel unwell

P314 Get Medical advice/attention if you feel unwell

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing

P305+P351+P338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact

lenses if present and easy to do – continue rinsing

P308+P313 IF exposed or concerned: Get medical advice/attention P337+P313 If eye irritation persists, get medical advice/attention

P405 Store locked up

P403+P233 Store in a well ventilated place. Keep container tightly closed

P501 Dispose contents/containers in accordance with local, state and federal regulations.

Signal Word: Danger





3. COMPOSITION/IFORMATION ON INGREDIENTS

Chemical Name	CAS number	Weight Concentration %
Feldspar	14808-60-7	14.00%
Feldspar	68476-25-5	14.00%

4. FIRST AID MEASURES

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if breathing is affected. If breathing is difficult, supply oxygen.

IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do so. If pain, blinking, or irritation develops or persists, get medical attention. Continue rinsing.

IF ON SKIN (or clothing): Remove affected clothing and wash all exposed skin with water for at least 15 minutes . If irritation develops or persists, get medical attention.

IF SWALLOWED: rinse mouth thoroughly. Do not induce vomiting without advice from poison control center or medical professional. Get medical attention if you feel unwell.

First-aid measures general: If exposed or concerned, get medical attention/advice. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before re-use. Never give anything to an unconscious person.

5. FIREFIGHTING MEASURES

Flash Point: N/A

LEL: UEL:

Suitable extinguishing media: Carbon dioxide, Alcohol foam, or dry chemical

Heat builds up pressure in closed containers and can rupture or explode.

Carbon Dioxide, Carbon Monoxide, partially burned Carbon, and acrid fumes.

Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Do not dispose of fire-fighting water in the environment.

Do not entire fire area without proper protective equipment, including respiratory protection

6. ACCIDENTAL RELEASE MEASURES

Stop leak at source when it is safe to do so. Use non-sparking tools only. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Prevent entry to sewers and public waters. Avoid release to the environment. Notify authorities if liquid enters sewers or public waters. This material and its container must be

SDS for: 750 Paste Page 2 of 5

disposed of in a safe way, and as per local legislation.

Absorb the liquid with inert material (such as dry sand or earth) and place it in a chemical waste container. Sweep or shovel spills into appropriate container for disposal.

Persons not wearing protective equipment should be evacuated from area of spill until cleanup has been completed. Dike and pump the liquid into waste containers.

7. HANDLING AND STORAGE

Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks, and open flames. Avoid breathing vapor and mist. Vapors of this material are heavier than air and will collect in low or confined areas. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

Store in a cool, well-ventilated place. Store at temperatures between 50°F-90°F unless otherwise stated. Product must remain in its original sealed containers with manufacturer's name and label in tact. Do not store materials in direct sunlight or where they may be damaged by water or rain. Dry goods (When applicable) must be kept dry. No Additional Data

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Feldspar 14808-60-7	PELs - (30)/(%SiO2 + 2) mg/m3 TWA total dust PELs - (250)/(%SiO2 + 5) mppcf TWA, respirable fraction PELs - (10)/(%SiO2 + 2) mg/m3 TWA, respirable fraction	0.025 mg/m3 TWA (respirable fraction)	Not Established
Feldspar 68476-25-5	OELs not established	OELs not established	Not Established

Use explosion-proof equipment with flammable materials.

Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended expsoure limits. Ensure adequate ventilation, especially in confined areas.

Hand proection: Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove materials are: Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate, PVC or vinyl. Suitable gloves for this specific application can be recommended by the glove supplier.

Eye protection: Wear eye protection, including chemical splash goggles and a face shield when possibility exists for eye contact due to spraying liquid or airborne particles.

Skin and body protection: Wear long sleeves, and chemically impervious PPE/coveralls to minimize bodily exposure . Respiratory proection: Use NIOSH-approved dust/particulate respirator. Where vapor, mist, or dust exceed PELs or other applicable OELs, use NIOSH-approved respiratory protective equipment.

Changed contamined clothing immediately. Wash contaminated clothing before reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Liquid

Vapor Pressure: 67.0 mm Hg @ 20C

Vapor Density: 1.8

Density: 1.01

Freezing point: Not Available

Boiling range: 100°C

Evaporation rate: Not Available

Odor: Slight

Odor: Slight

Odor threshold: Not Available

pH: Not Available

Melting point: Not Available

Solubility: Not Available

Flash point: 999 F,999 C

Flammability: Not Available

SDS for: 750 Paste Page 3 of 5

Explosive Limits: Not Available

Partition coefficient (n- Not Available

octanol/water):

Autoignition temperature: Not Available

Viscosity: Not Available

Decomposition temperature: Not Available

Grams VOC/liter less water 18.60

10. STABILITY AND REACTIVITY

STABLE

Incompatible materials

No Data Available / Not Applicable

Hazardous decomposition products

No Data Available / Not Applicable

Hazardous polymerization will not occur.

11. TOXICOLOGICAL INFORMATION

Mixture Toxicity
Component Toxicity

14808-60-7 Feldspar

Oral LD50: 500 mg/kg (Rat)

Toxicological Routes of Entry

Inhalation Skin Contact E

Eye Contact Ingestion

Specific Target Organs Toxicology

No Data Available / Not Applicable

Effects of Overexposure

Carcinogeniticy

<u>CAS Number</u> <u>Description</u> 14808-60-7 Feldspar Weight Carcinogen RatingFeldspar: IARC are

Feldspar: IARC group 1 - Carcinogenic to humans

12. ECOLOGICAL INFORMATION

No data available

Component Ecotoxicity

13. DISPOSAL CONSIDERATIONS

Waste treatment methods: Obtain the consent of pollution control authorities before discharging to wastewater treatment plants.

Waste disposal recommendations: Dispose in a safe manner in accordance with local/national regulations. Do not allow the product to be released into the environment.

14. TRANSPORT INFORMATION

SDS for: 750 Paste Page 4 of 5

<u>Agency Proper Shipping Name</u> <u>UN Number Packing Group Hazard Class</u>

DOT Not regulated for transport IATA Not regulated for transport IMDG Not regulated for transport

15. REGULATORY INFORMATION

U.S. Federal Regulations

State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

WARNING! This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

14808-60-7 Feldspar Carcinogens

The following chemicals are reportable under Sara 313

- None

<u>Country</u> <u>Regulation</u> <u>All Components Listed</u>

USA Toxic Substances Control Act (listed or exempt) Yes

16. OTHER INFORMATION

This information is provided in good faith and is correct to the best of AVM Industries' knowlege as of the date hereof and is designed to assist our customers; however, AVM makes no representation as to its completeness or accuracy. This product is intended for sale to mainly professional contractor. We require customers to satisfy themselves as to the suitability for their specific applications. Any use which AVM Industries customers or third parties make of this information, or any reliance on, or decisions made based upon it, are the responsibility of such customer or third party. AVM Industries disclaims responsibility for damages, or liability of any kind resulting from the use of this information. THERE ARE NO WARRANTIES OR REPRESENTATIONS, EXPRESS OR IMPLIED, INCLUDING THOSE OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THIS INFORMATION OR TO THE PRODUCT IT DESCRIBES. IN NO EVENT SHALL AVM INDUSTRIES BE LIABLE FOR SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES.

Reviewer Revision

Date Prepared: 9/22/2015

SDS for: 750 Paste Page 5 of 5

Printed: 9/22/2015 at 3:20:53PM