



AVM Acripatch 5020 Multi-Purpose Ready to Use Acrylic Patch

ICC ESR-2125,
L.A. RR#: 25430

Sections 071800 / 071813
Fluid Applied Waterproofing

Product Name

Elasto Fiberdeck® 100

Manufactured by

AVM Industries, Inc.
8245 Remmet Ave, Canoga Park, CA 91304
888.414.1041 818.888.0050
www.avmindustries.com

Product Description

AVM Acripatch 5020 is a high performance semi-rigid acrylic patch used in surface preparation as needed in many of AVM's waterproofing systems and tested as a component of the AVM System 100, Elasto Fiberdeck. (ICC ESR-2125 and L.A. RR#: 25430)

Where to Use

On new or existing concrete or plywood decks, to feather in flashing joints and other minor substrates imperfections. (For other substrates, consult with AVM Industries prior to installation.)

Warranty

Refer to each waterproofing system's warranty for details.

Delivery, Storage, and Handling

- Delivery of the Acripatch 5020 to the job site must be in their original sealed containers, with manufacturer's name and label intact.
- Handle and store containers in accordance with printed instructions.
- Store at temperatures between 50°F and 90°F. Do not store Primer 100 in direct sunlight or where it may be damaged by water or rain.
- Keep Acripatch 5020 out of the reach of children.
- If irritation occurs during use, liberally flush affected areas with water. If irritation continues, see a physician immediately.



Project Conditions

- Do not apply Acripatch 5020 at temperatures below 50°F, or if precipitation is imminent, or above 90°F if applying in direct sun light.
- Provide adequate ventilation during installation.
- Warn personnel against hazards of Acripatch 5020 to skin and eyes.
- Protect adjacent surfaces which could be damaged during the application.

System Application

Install the Acripatch 5020 in accordance with the Elasto Fiberdeck Installation Instructions. Allow Acripatch to fully cure before installing other coatings over it.

Substrates

Refer to the Elasto Fiberdeck installation instructions for more information.

Preparation of Substrates

The substrate surfaces must be structurally sound, clean, dry, free of contamination, and prepared according with the Elasto Fiberdeck Installation Instructions.

Installation

Typically Applied with a trowel or taping knife. Refer to the Elasto Fiberdeck installation instructions for details.

Quality Control

Refer to the Elasto Fiberdeck installation instructions for details.

Protection of Installed Work

Refer to the Elasto Fiberdeck installation instructions for details.

Clean Up

Tools may be cleaned with water before Acripatch 5020 is dry.

Availability and Cost

Contact AVM Industries or your approved distributor or applicator for pricing and availability.

Technical Services

Technical services are available by contacting our offices at: **888.414.1041** or **818.888.0050** or visit **www.avmindustries.com**

System Specifications

See next page.



The following coverages are based on controlled tests. Actual coverages may vary.

Materials	Coverage
AVM Acripatch 5020	Varies depending on thickness, substrate conditions and other factors

General Data - AVM Acripatch 5020

Shelf Life:	One year in original unopened packaging.
Storage Conditions:	Store dry at 50°-90°F. If frozen, discard
Color:	Standard Colors: (Un-tinted)

Item/Component	Packaging	Approximate Shipping Weights	VOC
AVM Acripatch 5020	2.0/5.0 gal. pails	15/39 lbs.	46 Grams/Liter

For a complete list of details in CAD or PDF, please visit our website at www.avmindustries.com.

AVM Industries, Inc.
8245 Remmet Ave, Canoga Park, CA 91304
888.414.1041 818.888.0050

Quality Waterproofing Products



www.avmindustries.com