



Aussie Membrane 570 - Hot Rubber

Heavy Duty Hot Applied Rubberized Asphalt Waterproofing Membrane

Topping Slabs Spec

Section 071400 - Fluid-Applied Waterproofing

Section 071413 - Hot Fluid-Applied Rubberized Asphalt Waterproofing

Section 075556 - Hot-Applied Rubberized Asphalt Protected Membrane Roofing

Product Name

Aussie Membrane 570 - Hot Rubber

By

AVM Industries, Inc.
8245 Remmet Ave, Canoga Park, CA 91304
888.414.1041 818.888.0050
www.avmindustries.com

Product Description

Aussie Membrane 570 - Hot Rubber, is a hot-applied asphalt-based composition membrane applied in a liquid state to form a continuous, seamless, tough, flexible, black, fully-adhered waterproofing membrane.

Aussie Membrane 570 - Hot Rubber exhibits excellent elongation and recovery properties and maintains excellent long term stability.

Where to Use

Over Portland cement structural concrete surfaces including precast and poured in place roofs, parking structures, Podium decks, bridge decks, etc. Other common waterproofing applications include between-slabs, under topping-slabs, green roofs, under roof paver systems, tunnels, re-roofs, and many other applications. **Aussie Membrane 570 - Hot Rubber** may also be used over gypsum and wood surfaces. Do not install **Aussie Membrane 570 - Hot Rubber** over structural light weight concrete without prior approval from AVM. Light Weight insulating concrete is not an approved substrate.



Warranty

AVM Industries will warranty the installed membrane for a period of five (5) years. Ten (10) year warranties are also available. For complete warranty details, contact AVM Industries or consult with your applicator.

Delivery, Storage, and Handling

- Delivery of the **Aussie Membrane 570 - Hot Rubber** must be delivered to the job site in their original sealed containers, with manufacturer's name, packaging and label intact.
- Handle and store containers in accordance with printed instructions.
- Store at temperatures between 50°F and 90°F. Do not store materials in direct sunlight or where they may be damaged by water or rain.
- Failure to comply with the recommended storage conditions may result in premature failure or damage of the product. For specific storage advice, please contact AVM Industries and/or its representatives.
- Keep all materials out of the reach of children.
- If irritation occurs during use, liberally flush affected areas with water. If irritation continues, see a physician immediately.

Safety Precautions & Hazards Associated With Hot-Applied Materials

For additional information, refer to **Aussie Membrane 570 - Hot Rubber** Installation Instructions and/or Safety Data Sheets. Or contact AVM Industries at 818-888-0050. www.avmindustries.com

Availability and Cost

Contact AVM Industries or your approved applicator for pricing and availability.

Technical Services

Technical services are available by contacting our offices at: **888.414.1041** or **818.888.0050** or visit www.avmindustries.com

System Specifications

See next page.

Property		Requirement	Test Method
Recommended application temperature		380°F-400°F (193°C-204°C)	
Flash Point, C.O.C.		500°F (260°C)	ASTM D 92
Cone Penetration	77°F (25°C)	≤110	CAN/CGSB 37.50-M89
	122°F (50°C)	≤200	CAN/CGSB 37.50-M89
Flow		≤3 mm Max	CAN/CGSB 37.50-M89
Toughness		≥5.5 Joule Min	CAN/CGSB 37.50-M89
Ratio of Toughness to Peak Load		≥0.040	CAN/CGSB 37.50-M89
Water Vapor Permeance		1.7 Ng/Pa. / Sq. Meter	CAN/CGSB 37.50-M89
Water Absorption		0.35g max gain or 0.18g max loss	CAN/CGSB 37.50-M89
Pinholing		One hole max	CAN/CGSB 37.50-M89
Low Temperature Flexibility		No Cracking	CAN/CGSB 37.50-M89
Crack Bridging Capability		No Cracking, Splitting or loss of Adhesion	CAN/CGSB 37.50-M89
Heat Stability		Shall meet penetration, flow, low-temp, flexibility and viscosity requirements	CAN/CGSB 37.50-M89
Viscosity at Application Temperature		2-15 seconds	CAN/CGSB 37.50-M89
Adhesion		Pass	CAN/CGSB 37.50-M89

Item/Component	Packaging	Approx Shipping Weights	Qty per pallet	Coverages	VOC
Hot Rubber	35 Lbs Box	35 lb/Box, 2100 lbs/pallet (22 pallets/truck)	60 Boxes/pallet	1.33 lbs/sq ft @215 mils	0 g/l
Primer-570 SB	5-Gal Bucket	41 lbs/Bucket (1525 lbs/pallet)	36 Buckets/pallet	400-500 sq ft/gal	75 g/l
Primer 570-WB	5-Gal Bucket	41 lbs/Bucket (1525 lbs/pallet)	36 Buckets/pallet	250-300 sq ft/gal	0 g/l
Mat 570	4'x360 Yards Roll	40.5 lbs/Roll (700 lbs/pallet)	16 Rolls/pallet	4,320 sq ft/roll	N/A

For a complete list of details in CAD or PDF, please visit our website at www.avmindustries.com.

AVM Industries, Inc.
8245 Remmet Ave, Canoga Park, CA 91304
888.414.1041 818.888.0050

Quality Waterproofing Products



www.avmindustries.com