



Aussie Guard™ Quality Assurance Program Warranty Requirements (Deck and Planter)

Aussie Guard™ Quality Assurance Program Warranty Requirements (Deck and Planter)

1. Aussie Guard™ product warranty eligibility

(reference Product Manuals for product applications and installation instructions):

- | | | | | |
|--|----------------|-----------------|-----------------|-----------------|
| • Aussie Membrane 500 & 502 (90 mil) | 5 Years | 10 Years | | |
| • Aussie Membrane 520 (90 mil) | 5 Years | 10 Years | | |
| • Aussie Membrane 500 & 502 (120 mil reinforced) | 5 Years | 10 Years | 15 Years | 20 Years |
| • Aussie Membrane 520 (120 mil reinforced) | 5 Years | 10 Years | 15 Years | 20 Years |
| • Aussie Membrane 570 (215 mil reinforced) | 5 Years | 10 Years | 15 Years | 20 Years |

All products require a protection layer and primer

All 90 Mil systems require ¼ inch slope to drain

2. Installer: AVM products must be installed by an AVM trained Approved Applicator

3. Project waterproofing details must be installed in accordance with AVM's standard published and project-specific waterproofing details. All details must be approved by the designer.

4. Pre-Installation Conference: A pre-installation conference shall be held before the commencement of field operations to establish procedures to maintain optimum working conditions and to coordinate this work with related and adjacent work. Agenda for the meeting shall include a review of special details and flashing.

Required Attendees: Waterproofing Manufacturer, Approved Applicator, Owners Representative, Architect, General Contractor, Concrete Contractor, Waterproofing Consultant, Electrical, Plumbing Contractors and all other relevant trades.

5. Inspection: Project must be inspected by an AVM approved 3rd Party Independent Inspection firm. Field reports should be completed and sent to all parties within 24 hours of the inspection. Inspection Requirements will be reviewed during pre-installation conference.

6. Leak Detection: Either 48-hour flood testing or electronic leak detection are required. Additional requirements may be needed for electronic leak detection depending on the application and substrate.

7. Warranty and Issuance:

- Issued upon substantial completion of the waterproofing system as defined in the technical documentation.
- All open Action Items must be addressed and verified by the independent Inspection Firm before project completion.
- Independent Inspection Firm must be paid in full
- Important Warranty Requirement: For warranties to be valid, all warranty request forms must be submitted no later than 60 days from Substantial Completion or Certificate of Occupancy. Failure to submit the appropriate warranty request form in time will result in a standard five-year material warranty.

