



# AVM Material Warranty Requirements (Deck and Planter)

1. \*AVM Material Warranty eligibility  
(reference Product Manuals for product applications and installation instructions):
  - Aussie Membrane 500 & 502 (90 mil) **5 Years 10 Years**
  - Aussie Membrane 520 (90 mil) **5 Years 10 Years**
  - Aussie Membrane 500 & 502 (120 mil reinforced) **5 Years 10 Years**
  - Aussie Membrane 520 (120 mil reinforced) **5 Years 10 Years**
  - Aussie Membrane 570 **5 Years 10 Years**
  
2. Project waterproofing details must be installed in accordance with AVM's standard published and/or project specific waterproofing details. Job specific details created by AVM Applicator or designer must be signed off by AVM Representative
  
3. Pre-Installation Conference: A pre-installation conference is recommended prior to commencement of field operations to establish procedures to maintain optimum working conditions and to coordinate this work with related and adjacent work. Agenda for meeting shall include review of special details and flashing.
  
4. Warranty and Issuance:
  - The Certified Date of Substantial Completion is required for warranty issuance.
  - \*All substrates must meet AVM requirements and be primed with the appropriate primer.
  - Important Warranty Requirement: For warranties to be valid, all warranty request forms must be submitted no later than 60 days from Substantial Completion or Certificate of Occupancy. Failure to submit the appropriate warranty request form in time will result in a standard five-year material warranty.

