Safety Data Sheet

AVM Industries Inc.

Version 1.1 Revision Date 8-5-15

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Aggregate 400 Product Code: Aggregate 400

AVM Industries, Inc.

8245 Remmet Ave, Canoga Park CA 91304-4133 Tel: (818) 888-0050 www.avmindustries.com Emergency Contact: Chemtrec (800) 424-9300

2. HAZARDS IDENTIFICATION

GHS Ratings:

	Skin corrosive	2	Reversible adverse effects in dermal tissue, Draize score:>= 2.3 < 4.0 or persistent inflammation			
	Eye corrosive	1	Serious eye damage: Irreversible damage 21 days after exposure, Draize score: Corneal opacity >= 3, Iritis > 1.5			
	Carcinogen	1A	Known Human Carcinogen Based on human evidence			
	Organ toxin single exposu	re 3	Transient target organ effects- Narcotic effects- Respiratory tract irritation			
	Organ toxin repeated exposure	1	Significant toxicity in humans- Reliable, good quality human case studies or epidemiological studies Presumed significant toxicity in humans- Animal studies with significant and/or severe toxic effects relevant to humans at generally low exposure (guidanc			
<u>GH</u>	<u>SHazards</u>					
	H315	Causes skin	irritation			
	H318	Causes serie	bus eye damage			
	H335	May cause r	espiratory irritation			
	H350	May cause o	ancer			
	H372	Causes dam	age to organs through prolonged or repeated exposure			
<u>GH</u>	S Precautions					
	P201	Obtain special instructions before use				
	P202	Do not handle until all safety precautions have been read and understood				
	P260	Do not breat	ne dust, mist or vapours			
	P261	Avoid breath	ing dust, mist, or vapours			
	P264	Wash hands	forearms and face thoroughly after handling			
	P270	Do not eat, o	rink or smoke when using this product			

P271	Use only outdoors or in a well-ventilated area
P280	Wear protective gloves, protective clothing, eye protection, and face protection
P281	Use personal protective equipment as required
P310	Immediately call a POISON CENTER or doctor/physician
P312	Call a POISON CENTER or doctor/physician if you feel unwell
P314	Get Medical advice/attention if you feel unwell
P321	Specific treatment (see first aid instructions on SDS and on this label)
P362	Take off contaminated clothing and wash before reuse
P302+P352	IF ON SKIN: Wash with soap and water
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for
	breathing
P305+P351+P338	IF IN EYES: Rinse continuously with water for several minutes. Remove contact
	lenses if present and easy to do – continue rinsing
P308+P313	IF exposed or concerned: Get medical advice/attention
P332+P313	If skin irritation occurs: Get medical advice/attention
P405	Store locked up
P403+P233	Store in a well ventilated place. Keep container tightly closed
P501	Dispose contents/containers in accordance with local, state and federal regulations.

Signal Word: Danger



3. COMPOSITION/IFORMATION ON INGREDIENTS

Chemical Name	CAS number	Weight Concentration %
Cement, portland, chemicals	65997-15-1	30.00%
Feldspar	14808-60-7	12.00%

4. FIRST AID MEASURES

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if breathing is affected. If breathing is difficult, supply oxygen.

IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do so. Get medical attention immediately. Continue rinsing.

IF ON SKIN (or clothing): Remove affected clothing and wash all exposed skin with water for at least 15 minutes . If irritation develops or persists, get medical attention.

IF SWALLOWED: rinse mouth thoroughly. Do not induce vomiting without advice from poison control center or medical professional. Get medical attention if you feel unwell.

First-aid measures general: If exposed or concerned, get medical attention/advice. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before re-use. Never give anything to an unconscious person.

5. FIREFIGHTING MEASURES

Flash Point: N/A

LEL:

UEL:

Suitable extinguishing media: Carbon dioxide, Alcohol foam, or dry chemical Heat builds up pressure in closed containers and can rupture or explode. Carbon Dioxide, Carbon Monoxide, partially burned Carbon, and acrid fumes. Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Do not dispose of fire-fighting water in the environment.

Do not entire fire area without proper protective equipment, including respiratory protection

6. ACCIDENTAL RELEASE MEASURES

Stop leak at source when it is safe to do so. Use non-sparking tools only. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Prevent entry to sewers and public waters. Avoid release to the environment. Notify authorities if liquid enters sewers or public waters. This material and its container must be disposed of in a safe way, and as per local legislation .

Absorb the liquid with inert material (such as dry sand or earth) and place it in a chemical waste container. Sweep or shovel spills into appropriate container for disposal.

Persons not wearing protective equipment should be evacuated from area of spill until cleanup has been completed. Dike and pump the liquid into waste containers.

7. HANDLING AND STORAGE

Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks, and open flames. Avoid breathing vapor and mist. Vapors of this material are heavier than air and will collect in low or confined areas. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

Store in a cool, well-ventilated place. Store at temperatures between 50°F-90°F unless otherwise stated. Product must remain in its original sealed containers with manufacturer's name and label in tact. Do not store materials in direct sunlight or where they may be damaged by water or rain. Dry goods (When applicable) must be kept dry. No Additional Data

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Cement, portland, chemicals 65997-15-1	PELs - 15 mg/m3 TWA (total dust) PELs - 5 mg/m3 TWA (respirable fraction) PELs - 50 mppcf TWA (<1% Crystalline silica)	TLV - 1 mg/m3 TWA (particulate matter containing no asbestos and <1% crystalline silica, respirable fraction)	Not Established
Feldspar 14808-60-7	PELs - (30)/(%SiO2 + 2) mg/m3 TWA total dust PELs - (250)/(%SiO2 + 5) mppcf TWA, respirable fraction PELs - (10)/(%SiO2 + 2) mg/m3 TWA, respirable fraction	0.025 mg/m3 TWA (respirable fraction)	Not Established

Use explosion-proof equipment with flammable materials.

Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended expsoure limits. Ensure adequate ventilation, especially in confined areas.

Hand proection: Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove materials are: Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate, PVC or vinyl. Suitable gloves for this specific application can be recommended by the glove supplier.

Eye protection: Wear eye protection, including chemical splash goggles and a face shield when possibility exists for eye contact due to spraying liquid or airborne particles.

Skin and body protection: Wear long sleeves, and chemically impervious PPE/coveralls to minimize bodily exposure . Respiratory proection: Use NIOSH-approved dust/particulate respirator. Where vapor, mist, or dust exceed PELs or other applicable OELs, use NIOSH-approved respiratory protective equipment.

Changed contamined clothing immediately. Wash contaminated clothing before reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Liquid Vapor Pressure: -99999 mmHg Vapor Density: -99999.0 Density: 2.76 Freezing point: Not Available Boiling range: 2230°C Evaporation rate: Not Available Explosive Limits: Not Available

Autoignition temperature: Not Available Viscosity: Not Available

10. STABILITY AND REACTIVITY

STABLE

Incompatible materials

No Data Available / Not Applicable

Hazardous decomposition products

No Data Available / Not Applicable Hazardous polymerization will not occur.

11. TOXICOLOGICAL INFORMATION

Mixture Toxicity Component Toxicity

14808-60-7

Feldspar Oral LD50: 500 mg/kg (Rat)

 Inhalation
 Skin Contact
 Eye Contact
 Ingestion

 Specific Target Organs Toxicology
 No Data Available / Not Applicable
 Ingestion

Effects of Overexposure

Carcinogeniticy

CAS Number 14808-60-7 <u>Description</u> Feldspar <u>% Weight</u> 12 <u>Carcinogen Rating</u> Feldspar: IARC group 1 -Carcinogenic to humans

Odor: Slight Odor threshold: Not Available

Melting point: Not Available

Solubility: Not Available

Flash point: 999 F,999 C

Flammability: Not Available

Partition coefficient (n- Not Available octanol/water):

Decomposition temperature: Not Available

Grams VOC/liter less water 0.00

pH: Not Available

12. ECOLOGICAL INFORMATION

No data available

Component Ecotoxicity

13. DISPOSAL CONSIDERATIONS

Waste treatment methods: Obtain the consent of pollution control authorities before discharging to wastewater

treatment plants.

Waste disposal recommendations: Dispose in a safe manner in accordance with local/national regulations . Do not allow the product to be released into the environment.

14. TRANSPORT INFORMATION

Agency Proper Shipping Name No Data Available / Not Applicable

<u>UN Number</u>

Packing Group Hazard Class

15. REGULATORY INFORMATION

U.S. Federal Regulations

State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): WARNING! This product contains the following chemicals which are listed by the State of California as

carcinogenic or a reproductive toxin:

14808-60-7 Feldspar Carcinogens

The following chemicals are reportable under Sara 313

- None

Country USA Regulation Toxic Substances Control Act (listed or exempt) All Components Listed Yes

16. OTHER INFORMATION

This information is provided in good faith and is correct to the best of AVM Industries' knowlege as of the date hereof and is designed to assist our customers; however, AVM makes no representation as to its completeness or accuracy. This product is intended for sale to mainly professional contractor. We require customers to satisfy themselves as to the suitability for their specific applications. Any use which AVM Industries customers or third parties make of this information, or any reliance on, or decisions made based upon it, are the responsibility of such customer or third party. AVM Industries disclaims responsibility for damages, or liability of any kind resulting from the use of this information. THERE ARE NO WARRANTIES OR REPRESENTATIONS, EXPRESS OR IMPLIED, INCLUDING THOSE OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THIS INFORMATION OR TO THE PRODUCT IT DESCRIBES. IN NO EVENT SHALL AVM INDUSTRIES BE LIABLE FOR SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES.

Reviewer Revision

Date Prepared: 9/22/2015