

AVM Aussie Grout 907

Remedial Bentonite/Polymer Grout Waterproofing

Sections 036000 / 036400

Injection Grout

Product Name

AVM Aussie Grout 907

Manufactured by

AVM Industries, Inc.
8245 Remmet Ave, Canoga Park, CA 91304
888.414.1041 818.888.0050
www.avmindustries.com

Product Description

AVM Aussie Grout 907 is an easy mixing, organic-free, high-solids bentonite/polymer grout engineered to seal water intrusion in existing below-grade structures. **Aussie Grout 907** is pumped to the exterior of the foundation wall where it sets into a dense gelatin state that forms a waterproofing barrier. **Aussie Grout 907** can be used to seal leaks in concrete, CMU block, brick and stone foundations.

Where to Use

- Foundation Walls
- Foundation Slabs
- Tunnels
- CMU and Brick Foundation Walls
- Manholes and Utility Vaults

Mixing and Application

Aussie Grout 907 should be mixed with a ChemGrout electrical vertical shaft paddle mixer or equivalent. **Aussie Grout 907** remains placeable for up to two hours and sets in eight hours.

To achieve a 30% solids slurry, add one 50 lb bag of grout to 14 gallons (22.7 kg bag of grout to 53 liters) of freshwater. This ratio will yield approximately 2.2 ft³ (62.2 liters).

Reference **Aussie Grout 907** Installation instructions for further details.



Delivery, Storage, and Handling

- Delivery of the Grout components must be in their original sealed bags, with manufacturer's name and label intact.
- Handle and store containers in accordance with printed instructions.
- Store at temperatures between 40°F and 90°F. Do not store materials where they may be damaged by water or rain.
- Keep all materials out of the reach of children. Do not take internally.
- Wear eye protection. Avoid eye contact or prolonged contact with skin. Wash thoroughly after handling. If irritation occurs during use, liberally flush affected areas with water. If irritation continues, see a physician immediately. Read all safety information before use.
- No Shelf Life. If material in the bag has clumps or is hard, discard.
- Non-Flammable.
- Unregulated for transport -no hazmat shipping required.

Project Conditions

- Provide adequate ventilation during installation.
- Protect adjacent surfaces which could be damaged during the application.
- Contact AVM for recommendation if there is a full-time dewatering system

Availability and Cost


Contact AVM Industries or your approved applicator for pricing and availability.

Technical Services

Technical services are available by contacting our offices at: **888.414.1041** or **818.888.0050** or visit www.avmindustries.com

System Specifications


See next page.



Technical Data/Properties

Property	Value	Test
Bulk Density (Mixed)	75.55 lbs/ft ³	
Solids (Mixed)	30%	
Permeability Range	1x10 ⁻⁷ to 1x10 ⁻⁹ cm/sec	ASTM D5084
Yield per Bag	2.2 ft ³ (62.2 liters)	
Color	Grey	

Item / Component	Packaging	Approx Shipping Weights	VOC
Aussie Grout 907	48 Bags/Pallet	50.0 Lbs	0 Grams/Liter



For a complete list of details in CAD or PDF, please visit our website at www.avmindustries.com.

AVM Industries, Inc.
 8245 Remmet Ave, Canoga Park, CA 91304
 888.414.1041 818.888.0050

Quality Waterproofing Products



www.avmindustries.com