



Aussie Bond 930 Clear Adhesive Spray Thermal and Moisture Protection

Section 071000

Product Name

Aussie Bond 930

Manufactured by

AVM Industries, Inc.
8245 Remmet Ave, Canoga Park, CA 91304
888.414.1041 818.888.0050
www.avmindustries.com

Product Description

Aussie Bond 930 wide web spray adhesive is one of the highest performance aerosol adhesives available. For temporary or permanent bonding, this high solid, fast tacking, low soak-in product is ideal for smooth, uneven or porous surfaces. Waterproof, flexible, transparent and non-staining, use this product for your toughest adhesive application with materials such as metal, wood, fiberglass insulation, plastic foams, leather, cardboard, most plastic, polyethylene sheeting, and cloth. This product contains NO CHLORINATED SOLVENTS OR OZONE DEPLETERS.

Where to Use

AVM Aussie Bond 930 adhesive spray is primarily used as an accessory product to the Aussie Skin 550G/560G waterproofing system and to adhere drainboard or insulation in waterproofing applications. Not intended for use on Vinyl.

Directions

Always shake well before using. Never aim valve at face. Hold can upright and apply adhesive in a side-to-side motion 10-14 inches from surface. Surface should be clean and dry. Spray at 60°F - 90°F for best results. After each use tip can upside down and press tip until spray is free of adhesive. For more permanent bonds, apply adhesive to both surfaces to be mated, allow adhesive to tack and then press together. Wipe tip clean while adhesive is wet. Dry adhesive can be cleaned up with mineral spirits.

Adequate Tests

We believe the information contained herein is correct to the best of our knowledge and tests. The recommendations and suggestions made herein are made without guarantee and representation as to results. We recommend that you perform adequate tests to determine if this product meets all of your requirements. The warranted shelf life of our products is twelve months from date of shipment to the original purchaser or as otherwise provided on the certificate of analysis.

Delivery, Storage, and Handling

- Delivery of the **Aussie Bond 930** Clear Adhesive Spray Cans to the job site must be in their original sealed containers, with manufacturer's name and label intact.
- Shelf Life: Twelve months from date of manufacture when properly stored.
- Store in a well-ventilated place. Keep containers tightly closed. Store locked up. Store at temperatures between 50°F and 90°F. Do not store materials in direct sunlight or where they may be damaged by water or rain.
- Failure to comply with the recommended storage conditions may result in premature deterioration of the product.
- Keep all materials out of the reach of children.
- Disposal: Dispose of contents/containers at an approved waste disposal facility.

Quality Control

- Visually inspect all coated surfaces to ensure a full and proper application, especially at penetrations, seams, corners, drainage footings and other hard-to-reach areas.
- All unsatisfactory areas shall be repaired prior to final acceptance.

Limited Warranty

AVM Industries, Inc. warrants that each of its products will be manufactured in accordance with the specifications in effect on the date of manufacture. WE MAKE NO OTHER WARRANTIES AND EXPRESSLY DISCLAIM ANY WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If a product fails to meet this limited warranty, purchaser's sole and exclusive remedy is replacement of the product or, at our option, refund of the purchase price. For additional warranty claim information, call 818-888-0050.

Compliance

CA Proposition 65: This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm.

U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List.

U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List.

This product contains **no chlorinated solvents of ozone depleters.**

Availability and Cost

Contact AVM Industries or your approved applicator for pricing and availability.

Technical Services

Technical services are available by contacting our offices at: **888.414.1041** or **818.888.0050** or visit **www.avmindustries.com**

System Specifications

See next page.



Technical Data/Properties

Property	Value
Coverage	35-40 sq.ft./can.
Bonding Time	0 to 5 minutes
Service temperature limits: (Temp at coated surface)	-40°F to 180°F (-40°C to 82°C)
Wet Flammability (ASTM D 3278)	Flash Point -40°F (-40°C)

Meets ASTM C916, Type IV (ASC-A-7001A, Type IV) Requirements

Aussie Bond 930 meets the standard for web spray aerosol adhesive when the requirement is less than 55% VOC.

Contains no Asbestos, lead, mercury or mercury compounds.

Leed: Meets the requirements of LEED 2009 Certification: Indoor Environmental Quality - Credit 4.1
(Low Emitting Materials: Adhesives and Sealants)

Item	Qty / Box	Weight / Box	Boxes / Pallet	Cans / Pallet	Pallet Weight
Spray Can (12 Oz. 340 Grams. 20 Fl. Oz. 592 mL.)	12	12.6 Lbs	85	1020	1150 Lbs

For a complete list of details in CAD or PDF, please visit our website at www.avmindustries.com.

AVM Industries, Inc.
8245 Remmet Ave, Canoga Park, CA 91304
888.414.1041 818.888.0050

Quality Waterproofing Products



www.avmindustries.com