



# AVM Material Warranty Requirements (Below Grade)

## 1. AVM Material Warranty eligibility

(reference Product Manuals for product applications and installation instructions):

- Aussie Membrane 500 & 502 **Up to 10 Years**
- Aussie Membrane 520 **Up to 10 Years**
- Aussie Skin 550G/560G **Up to 10 Years**
- Aussie Skin 550G/560G (Dual Membrane) **Up to 10 Years**
- Aussie Skin 550G/560G & 580 combined system **Up to 10 Years**
- Aussie Skin 550G/560G Pre-applied system\* **Up to 10 Years**
- Aussie Clay 590 **Up to 10 Years**

\*Additional products required for Shotcrete applications

2. Project waterproofing details must be installed in accordance with AVM's standard published and/or project specific waterproofing details. Job specific details created by AVM Applicator or designer must be signed off by AVM Representative.

3. Pre-Installation Conference: A pre-installation conference is recommended prior to commencement of field operations to establish procedures to maintain optimum working conditions and to coordinate this work with related and adjacent work. Agenda for meeting shall include review of special details and flashing.

## 4. Warranty and Issuance:

- The Certified Date of Substantial Completion is required for warranty issuance.
- Important Warranty Requirement: For warranties to be valid, all warranty request forms must be submitted no later than 60 days from Substantial Completion or Certificate of Occupancy. Failure to submit the appropriate warranty request form in time will result in a standard five-year material warranty.

