

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION OFFICE OF THE STATE FIRE MARSHAL FIRE ENGINEERING & INVESTIGATIONS DIVISION BUILDING MATERIALS LISTING PROGRAM

LISTING SERVICE

wear surface installed over polymer modified concrete covering 2.5 lbs/sq. yd. of galvanized metal la installed over a minimum 5/8" plywood substrate. Refer to manufacturer's installation instructions and product data sheets. *Tested in accordance with ASTM E84 with an additional 20 minute period Class A Flame Spread Index: 10 Smoke Developed Index: 10 Max Flame Front: 9 feet INSTALLATION:		
LISTEE: AVM Industries, Inc. 8245 Remmet Ave, Canoga Park, CA, 91304 Contact: Rudyan,Amir Email: amir@avmindustries.com DESIGN: Forevercoat 100 Walking Deck System. Product consists of a waterproofing system with a cementiti wear surface installed over polymer modified concrete covering 2.5 lbs/sq. yd. of galvanized metal le installed over a minimum 5/8" plywood substrate. Refer to manufacturer's installation instructions and product data sheets. RATING: *Tested in accordance with ASTM E84 with an additional 20 minute period Class A Flame Spread Index: 10 Smoke Developed Index: 10 Max Flame Front: 9 feet INSTALLATION: In accordance with listee's printed installation instructions, applicable codes and ordinances, and in manner acceptable to the authority having jurisdiction.	LISTING No.:	8110-2336:0501
Contact: Rudyan,Amir Email: amir@avmindustries.com DESIGN: Forevercoat 100 Walking Deck System. Product consists of a waterproofing system with a cementiti wear surface installed over polymer modified concrete covering 2.5 lbs/sq. yd. of galvanized metal lainstalled over a minimum 5/8" plywood substrate. Refer to manufacturer's installation instructions and product data sheets. RATING: *Tested in accordance with ASTM E84 with an additional 20 minute period Class A Flame Spread Index: 10 Smoke Developed Index: 10 Max Flame Front: 9 feet INSTALLATION: In accordance with listee's printed installation instructions, applicable codes and ordinances, and in a manner acceptable to the authority having jurisdiction.	CATEGORY:	8110 - DECKING FOR WILDLAND URBAN INTERFACE (W.U.I)
Forevercoat 100 Walking Deck System. Product consists of a waterproofing system with a cementiti wear surface installed over polymer modified concrete covering 2.5 lbs/sq. yd. of galvanized metal la installed over a minimum 5/8" plywood substrate. Refer to manufacturer's installation instructions and product data sheets. *Tested in accordance with ASTM E84 with an additional 20 minute period Class A Flame Spread Index: 10 Smoke Developed Index: 10 Max Flame Front: 9 feet INSTALLATION: In accordance with listee's printed installation instructions, applicable codes and ordinances, and in amanner acceptable to the authority having jurisdiction.	LISTEE:	Contact: Rudyan,Amir
RATING: *Tested in accordance with ASTM E84 with an additional 20 minute period Class A Flame Spread Index: 10 Smoke Developed Index: 10 Max Flame Front: 9 feet INSTALLATION: In accordance with listee's printed installation instructions, applicable codes and ordinances, and in a manner acceptable to the authority having jurisdiction.	DESIGN:	Forevercoat 100 Walking Deck System. Product consists of a waterproofing system with a cementitious wear surface installed over polymer modified concrete covering 2.5 lbs/sq. yd. of galvanized metal lath installed over a minimum 5/8" plywood substrate.
*Tested in accordance with ASTM E84 with an additional 20 minute period Class A Flame Spread Index: 10 Smoke Developed Index: 10 Max Flame Front: 9 feet INSTALLATION: In accordance with listee's printed installation instructions, applicable codes and ordinances, and in a manner acceptable to the authority having jurisdiction. MARKING:		Refer to manufacturer's installation instructions and product data sheets.
Flame Spread Index: 10 Smoke Developed Index: 10 Max Flame Front: 9 feet INSTALLATION: In accordance with listee's printed installation instructions, applicable codes and ordinances, and in a manner acceptable to the authority having jurisdiction. MARKING:	RATING:	*Tested in accordance with ASTM E84 with an additional 20 minute period
Smoke Developed Index: 10 Max Flame Front: 9 feet INSTALLATION: In accordance with listee's printed installation instructions, applicable codes and ordinances, and in a manner acceptable to the authority having jurisdiction. MARKING:		Class A
Max Flame Front: 9 feet INSTALLATION: In accordance with listee's printed installation instructions, applicable codes and ordinances, and in a manner acceptable to the authority having jurisdiction. MARKING:		Flame Spread Index: 10
INSTALLATION: In accordance with listee's printed installation instructions, applicable codes and ordinances, and in a manner acceptable to the authority having jurisdiction. MARKING:		Smoke Developed Index: 10
In accordance with listee's printed installation instructions, applicable codes and ordinances, and in a manner acceptable to the authority having jurisdiction. MARKING:		Max Flame Front: 9 feet
	INSTALLATION:	In accordance with listee's printed installation instructions, applicable codes and ordinances, and in a manner acceptable to the authority having jurisdiction.
	MARKING:	Listee's name, model number, rating, and SFM label.
APPROVAL: Listed as decking material for use in the Wildland Urban Interface areas. Refer to listee's Installation Instruction Manual for details.	APPROVAL:	Listed as decking material for use in the Wildland Urban Interface areas. Refer to listee's Installation Instruction Manual for details.
NOTES:	NOTES:	

*Revision 1-5-22 VWW



CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION OFFICE OF THE STATE FIRE MARSHAL FIRE ENGINEERING & INVESTIGATIONS DIVISION BUILDING MATERIALS LISTING PROGRAM

LISTING SERVICE



This listing is based upon technical data submitted by the applicant. OSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other suitable information sources.

Date Issued: 03/01/2023 Listing Expires: 06/30/2024

Authorized By: **Victor Wong**, Program Coordinator Fire Engineering & Investigations Division