



Dry Mil Thickness and Coverage Chart*

Dry Mil Thickness	Percent Solids							
	100%	90%	80%	70%	60%	50%	40%	30%
	Coverages (In Sq.Ft./Gal)							
1	1600.0	1400.0	1280.0	1120.0	960.0	800.0	640.0	480.0
2	800.0	720.0	640.0	569.0	480.0	400.0	320.0	240.0
3	533.0	480.0	426.5	373.0	320.0	267.3	213.3	160.0
4	400.0	360.0	320.0	280.0	240.0	200.0	160.0	120.0
5	320.0	288.0	256.0	224.0	192.0	160.0	128.0	96.0
10	160.0	144.0	128.0	112.0	96.0	80.0	64.0	48.0
15	106.7	96.0	85.3	74.7	64.0	53.5	42.7	32.0
20	80.0	72.0	64.0	56.0	48.0	40.0	32.0	24/0
25	64.0	57.6	51.2	44.8	38.4	32.0	25.6	19/2
30	53.3	48.0	42.7	37.3	32.0	26.7	21.3	16/0
35	45.7	41.1	36.6	32.0	27.4	22.9	18.3	13.7
40	40.0	36.0	32.0	28.0	24.0	20.0	16.0	12.0
45	35.8	32.0	28.4	24.9	21.3	17.8	14.2	10.7
50	32.0	28.8	25.6	22.4	19.2	16.0	12.8	9.8
55	29.1	26.2	23.3	20.4	17.5	14.5	11.6	8.7
60	26.6	24.0	21.3	18.7	16.0	13.3	10.7	8.0
62.5 (1/16")	25.6	23.0	20.5	17.9	15.4	12.8	10.2	7.7
70	22.9	20.6	18.3	16.0	13.7	11.4	9.1	6.9
75	21.3	19.2	17.1	14.9	12.8	10.7	8.5	6.4
80	20.0	18.0	16.0	14.0	12.0	10.0	8.0	6.0
125 (1/8")	12.8	11.5	10.2	9.0	7.7	6.4	5.1	3.8
250 (1/4")	6.4	5.8	5.1	4.5	3.8	3.2	2.6	1.9
375 (3/8")	4.3	3.8	3.4	3.0	2.6	2.1	1.7	1.3

* 128 Oz per Gallon

AVM Industries, Inc.
 8245 Remmet Ave, Canoga Park, CA 91304
 888.414.1041 818.888.0050

Quality Waterproofing Products

www.avmindustries.com

